

WiN7000-2 System Specifications

Radio and Modem:

Frequency	WiN7013-2: 1350 MHz to 1400 MHz WiN7014-2: 1400 MHz to 1500 MHz WiN7025-2: 2496 MHz to 2690 MHz WiN7035-2: 3400 MHz to 3600 MHz WiN7037-2: 3600 MHz to 3800 MHz
Radio Access Method	IEEE802.16-2005 (16e OFDMA)
Compatibility	WiMAX Forum Wave 2 Profile
Operation Mode	TDD
Channel Bandwidth	3.5Mhz, 5 MHz, 7MHz, 10 MHz
Frequency Resolution	0.125 MHz
Antennas	Integral Omni External Sector
Number of Antennas	2
Default Antenna	Omni
Antennas Connectors	2x N-Type, 50 ohm, lightning protected
Diversity Support	STC/MIMO
Output Power [P1dB]	2 x 10W; 2 x 45W; 2 x 90W
Output Power (average)	Type 10W: 30 dBm +/-1dB maximum Type 45W: 36 dBm +/-1dB maximum Type 90W: 39 dBm +/-1dB maximum
FFT/Modulation	512/1024 FFT points; QPSK, 16QAM, 64QAM
FEC	Convolution Code and Turbo Code
TPC	15dB

Network Interfaces:

Network	1. 40.5-60VDC 2. 10/100BaseT Half/full Duplex IEEE 802.3 CSMA/CD Fiber optic - optional
ASN GW Compatibility	WiMAX Forum R6 Profile C Compatible with CISCO ASN-GW

Configuration and Management:

Management	SNMP
SNMP Agent	SNMP ver 2 client: MIB II (RFC 1213), Private Win-Max MIBs
Software Upgrade	FTP
Remote Configuration	FTP

Mechanical:

Dimensions [HxWxD]	60cm x 27cm x 10cm
Weight	<12Kg

Power Interface:

Input	48VDC
Power Consumption	Type 10W: 75Watt maximum Type 45W: 140Watt maximum Type 90W: 216Watt maximum

Environmental:

Operating Temperature	-40°C to +55°C
Operating Humidity	5%-95% non condensing, Weather protected

Standards Compliance:

EMC	FCC part 15, subpart B, class B ETSI EN 301489-1/4
Safety	TUV-UL 60950-1 IEC 61950-1
Environmental	ETS 300 019: Part 2-1 T 1.2 & part 2-2 T 2.3 Part 2-4 T 4.1E IP66
Immunity	EN61000-4-3 EN61000-4-4 EN61000-4-5
Radio	FCC Part 27 ETSI EN302 326

Ordering Information:

Part Number	WiN70XX-2-Y-ZZE-W
XX – Frequency range	See frequency table for details
Y – Sync. Interface	E – IEEE1588; G – GPS
ZZ – PA peak power [Watt]	10; 45; 90

All information contained herein is believed to be accurate and is subject to change without notice. No responsibility is assumed for its use. WiNetworks reserves the right to make changes without notice, to product design, product components, and product manufacturing methods. Some specific combinations of options may not be available. All rights reserved. Please contact WiNetworks for further information.